

Q.UANTUM

QVOIP SERIES VOIP WEB BROWSER TELEPHONE ENTRY



- No Phone Bill with Google Voice, Unlimited calls in United States and Canada Only

- * Google Voice and the Google logo are registered trademarks of Google Inc.
- * Must have Internet Connection
- * Must sign-up for free Google Voice Account

Use your existing VOIP Provider.

For Commercial and residential, programmable via Web Browser.

No "Software Installation" necessary

Four way to program, via LAN, WAN, Direct Connect or System's Keypad.

Selectable port, no "Dedicated Static IP" required.

Indoor or Outdoor, Surface or Full-Flush Mount.

 **PACHCO**

Since 1978

Home of Telephone Entry Access Control Systems

San Clemente, California

1-888-678-7224

www.pach-co.com

FEATURES/MODEL	QVOIP Surface	QVOIPFF Full Flush	Q5VOIP Surface	Q5VOIPFF Full Flush
Google Voice free Unlimited USA and CANADA ONLY	●	●	●	●
Use Existing VOIP Not Free Service	●	●	●	●
<ul style="list-style-type: none"> • Analog Terminal Adapter must be installed in protective area. • Pach and Company does not warranty compatibility with your existing VOIP provider 				
QWCM IP Browser	●	●	●	●
Input power 12Vac transformer supplied	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc
Current consumption	900mA	900mA	1150mA	1150mA
Operating temperature	0-140 °F	0-140 °F	0-140 °F	0-140 °F
1x16 Backlit LCD display	●	●	●	●
Backlit keypad button	●	●	●	●
Tenant capacity	600	600	10	10
Access code capacity 4-8 digit	600	600	100	100
Automatic Call Forwarding	n/a	n/a	●	●
Intercom Mode	n/a	n/a	●	●
Card/Fob capacity	3000	3000	100	100
Number of Built-in relay form C dry contact	2	2	2	2
26-Bit Wiegand input	●	●	●	●
Built-in 26-Bit <i>proprietary</i> card reader	●	●	●	●
10 - Time Zone				
10 - Auto unlock schedule				
20 - Holiday time zone				
10 - Unlock hold card				
10 - Unlock hold code 4-8 digit				
10 - Temporary card up to 10 times used				
10 - Temporary code 4-8 digit up to 10 times used				
2 - Auxiliary input for exit switch, postal lock				
2 - Door sensor				
Unlock hold timer	●	●	●	●
Event recording buffer	600	600	600	600
Satellite Keypad, Card Reader or Combo w/ independent access	max. 8	max. 8	max. 8	max. 8
Surface mount dimension	6-7/16"(H) x 10-3/8"(W) x 2-3/4"(D)			
Full-flush mount dimension	Outside: 9-13/16"(H) x 11-13/16"(W) Inside: 7-1/2"(H) x 10-1/2"(W) x 3"(D)			
Warranty	24 month			
ACCESSORIES				
QVPC Analog color camera USCR 26-Bit Wiegand Satellite Card Reader USKP Satellite keypad UFOB Quantum Keyfob UCLAM Quantum Clam Shell Card UIISO Quantum ISO Card UCRM 26-Bit Wiegand/RS-485 controller Module UWCR 26-Bit Wiegand Reader	<u>Pedestal Mounting Post, Adapter Plate and Mounting Ring</u> UPM1S Standard Single Arm (42"H, 5"x5" base) UPM4S Standard Single Arm (47"H, 5"x5" base) UPM1L Large Single Arm (47"H, 8"x8" base) UPM6L Large Single Arm (64"H, 8"x8" base) UPM2 Double Vertical Arm (44"/84"H, 8"x8" base) UPM5 Double Horizontal Arm (47"H, 8"x8" base) UPMDB64 Single Arm Direct Buriel (64"H)			