

# Q. QUANTUM

## IP WEB BROWSER TELEPHONE ENTRY SYSTEM

### Q9000IP SERIES



Commercial application telephone entry system, programmable via Web Browser.

No "Software Installation" necessary

Postal Lock Ready

Four way to program, via LAN, WAN, Direct Connect or System's Keypad.

Selectable port, no "Dedicated Static IP" needed.

Surface or Full-Flush Mount

 **PACHCO**  
Since 1978

Home of Telephone Entry Access Control Systems

San Clemente, California  
1-888-678-7224  
[www.pach-co.com](http://www.pach-co.com)

FEATURES/MODEL	Q9000IP Surface Mount	Q9000IPFF Full-Flush Mount
Input Power	12Vac/12Vdc, 12Vac transformer included	12Vac/12Vdc, 12Vac transformer included
Current Consumption	1000mA	1000mA
Operating Temperature	0-140 °F	0-140 °F
Liquid Crystal Display	2 x16, 9mm	2 x16, 9mm
Backlit Keypad	Yes	Yes
Tenant Capacity	900	900
Access Code Capacity 4-8 Digit	900	900
Card/Keyfob Capacity	2000	2000
Number of Built-in Relay Form C Dry Contact	2	2
26-Bit Wiegand Input	Yes	Yes
Auto Unlock Schedule	10	10
Time Zone	10	10
Unlock Hold Using Card/Code	10	10
Holiday Time Zone	20	20
Temporary Card/Code up tp 10 Times Used	10	10
Programable Auxiliary Input	2	2
Door Sensor	2	2
Built-in Postal Lock Swich	Yes	Yes
Unlock Hold Timer	Yes	Yes
Event Recording/Report	1200 Buffer	1200 Buffer
Satellite Access Control Card Reader, Keypad, or Combo	Up to 8	Up to 8
Surface Mount Dimension (HxWxD)	13-9/16 " x 11-1/4 " x 3-3/4 "	
Full-Flush Dimension		Unit: 13-7/8" x 11-9/16" x 3-3/4" Trim Ring Inside: 13-3/4" x 12" x 3-11/16" Trim Ring Outside: 18" x 15-5/8"
Warranty	24 month	24 month

## ACCESSORIES

<b>QVPC</b> Analog color camera <b>USCR</b> 26-Bit Wiegand Satellite Card Reader <b>USKP</b> Satellite keypad <b>QSK1000</b> Satellite Card Reader and Keypad Combination <b>UFOB</b> Quantum Keyfob <b>UCLAM</b> Quantum Clam Shell Card <b>UIISO</b> Quantum ISO Card <b>UCRM</b> 26-Bit Wiegand/RS-485 controller Module	<a href="#">Pedestal Mounting Post, Adapter Plate and Mounting Ring</a> <b>UPM1S</b> Standard Single Arm (42"H, 5"x5" base) <b>UPM4S</b> Standard Single Arm (47"H, 5"x5" base) <b>UPM1L</b> Large Single Arm (47"H, 8"x8" base) <b>UPM6L</b> Large Single Arm (64"H, 8"x8" base) <b>UPM2</b> Double Vertical Arm (44"/84"H, 8"x8" base) <b>UPM5</b> Double Horizontal Arm (47"H, 8"x8" base) <b>UPM12E</b> 12" Expansion Arm use for all UPM	<b>UPMDB64</b> Single Arm Direct Buriel (64"H) <a href="#">Miscellaneous Accessories</a> <b>USP1</b> AC and Telephone Surge Protector. <b>USP2L</b> Surge and Lightning Protection, <i>include Lightning on 24 months warranty</i> <b>UBAT1</b> 12VDC 4.5 Ahr backup battery. <b>UXIT</b> Multipurpose pust button switch
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------