

QUANTUM QVOIP SERIES

WEB BROWSER GOOGLE VOICE TELEPHONE ENTRY SYSTEM



- No Phone Bill with Google Voice, Unlimited calls in United States and Canada Only

* Google Voice and the Google logo are registered trademarks of Google Inc.

* Must have Internet Connection

* Must sign-up for free Google Voice Account

Use your existing VOIP Provider.

For Commercial and residential, programmable via Web Browser.

No "Software Installation" necessary

Four way to program, via LAN, WAN, Direct Connect or System's Keypad.

Selectable port, no "Dedicated Static IP" required.

Indoor or Outdoor, Surface or Full-Flush Mount.

FEATURES/MODEL	QVOIP Surface	QVOIPFF Full Flush	Q5VOIP Surface	Q5VOIPFF Full Flush
Google Voice free Unlimited USA and CANADA ONLY	yes	yes	yes	yes
Use Existing VOIP Not Free Service	yes	yes	yes	yes
<ul style="list-style-type: none"> Analog Terminal Adapter must be installed in protective area. Pach and Company does not warranty compatibility with your existing VOIP provider 				
QWCM IP Browser	yes	yes	yes	yes
Input power 12Vac transformer supplied	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc	12Vac/12Vdc
Current consumption	1150mA, 1000mA (ATA)	1150mA, 1000mA (ATA)	1150mA, 1000mA (ATA)	1150mA, 1000mA (ATA)
Operating temperature	0-140 °F	0-140 °F	0-140 °F	0-140 °F
16 x 1 Backlit LCD display	yes	yes	yes	yes
Backlit keypad button	yes	yes	yes	yes
Tenant capacity	600	600	10	10
Access code capacity 4-8 digit	600	600	100	100
Automatic Call Forwarding	n/a	n/a	yes	yes
Intercom Mode	n/a	n/a	yes	yes
Card/Fob capacity	3000	3000	100	100
Number of Built-in relay form C dry contact	2	2	2	2
26-Bit Wiegand input	yes	yes	yes	yes
Built-in 26-Bit <i>proprietary</i> card reader	yes	yes	yes	yes
10 - Time Zone				
10 - Auto unlock schedule				
20 - Holiday time zone				
10 - Unlock hold card				
10 - Unlock hold code 4-8 digit				
10 - Temporary card up to 10 times used				
10 - Temporary code 4-8 digit up to 10 times used				
2 - Auxiliary input for exit switch, postal lock				
2 - Door sensor				
Unlock hold timer	yes	yes	yes	yes
Event recording buffer	600	600	600	600
Satellite Keypad, Card Reader or Combo w/ independent access	max. 8	max. 8	max. 8	max. 8
Surface mount dimension	6-7/16"(H) x 10-3/8"(W) x 3-1/2"(D)			
Full-flush mount dimension	Outside: 9-13/16"(H) x 11-13/16"(W) Inside: 7-1/2"(H) x 10-1/2"(W) x 3-5/8"(D)			
Warranty	24 month			
ACCESSORIES				
QVPC Analog color camera USCR 26-Bit Wiegand Satellite Card Reader USKP Satellite keypad USKPR Satellite Card Reader and Keypad Combination UFOB Quantum Keyfob UCLAM Quantum Clam Shell Card UIISO Quantum ISO Card UCRM 26-Bit Wiegand/RS-485 controller Module Miscellaneous Accessories USP1 AC and Telephone Surge Protector. USP2L Surge and Lightning Protection, <i>include Lightning on 24 months warranty</i>		UBAT1 12VDC 4.5 Ahr backup battery. UXIT Multipurpose push button switch IREXIT Infrared exit switch AHP5 Heater-pad Pedestal Mounting Post, Adapter Plate and Mounting Ring UPM1S Standard Single Arm (42"H, 5"x5" base) UPM1L Large Single Arm (47"H, 8"x8" base) UPM6L Large Single Arm (64"H, 8"x8" base) UPM2 Double Vertical Arm (44"/84"H, 8"x8" base) UPM5 Double Horizontal Arm (47"H, 8"x8" base) UPMDB64 Single Arm Direct Burial (64"H)		