

QUANTUM Q9000VOIP SERIES

WEB BROWSER GOOGLE VOICE TELEPHONE ENTRY SYSTEM



"No Phone Bill" with Google Voice, Unlimited calls in United States and Canada

* Google Voice and the Google logo are registered trademarks of Google Inc.

* Must have Internet Connection

* Must sign-up for free Google Voice Account

Commercial application telephone entry system, programmable via Web Browser.

No "Software Installation" necessary and No "Monthly" service

Postal Lock Ready

Four way to program, via LAN, WAN, Direct Connect or System's Keypad.

Selectable port, no "Dedicated Static IP" needed.

Surface or Full-Flush Mount

 **PACH AND COMPANY INC.**
SAN CLEMENTE, CALIFORNIA ■ 1-888-678-7224 ■ 949-498-2951

FEATURES/MODEL	Q9000VOIP Surface Mount	Q9000VOIPFF Full-Flush Mount
Input Power	12Vac/12Vdc, 12Vac transformer included	12Vac/12Vdc, 12Vac transformer included
Current Consumption	1200mA (main), 1000mA (ATA)	1200mA (main), 1000mA (ATA)
Operating Temperature	0-140 °F	0-140 °F
Google Voice Free calls USA and Canada	Yes Analog Terminal Adapter Included	Yes Analog Terminal Adapter Included
Liquid Crystal Display	16 x 2, 9mm	16 x 2, 9mm
Backlit Keypad	Yes	Yes
Tenant Capacity	900	900
Access Code Capacity 4-8 Digit	900	900
Card/Keyfob Capacity	2000	2000
Number of Built-in Relay Form C Dry Contact	2	2
26-Bit Wiegand Input	Yes	Yes
Auto Unlock Schedule	10	10
Time Zone	10	10
Unlock Hold Using Card/Code	10 cards/10 codes	10 cards/10 codes
Holiday Time Zone	20	20
Temporary Card/Code up to 10 Times Used	10 cards/10 codes	10 cards/10 codes
Programable Auxiliary Input	2	2
Door Sensor	2	2
Built-in Postal Lock Switch	Yes	Yes
Unlock Hold Timer	Yes	Yes
Event Recording/Report	1200 Buffer	1200 Buffer
Satellite Access Control Card Reader, Keypad, or Combo	Up to 8	Up to 8
Surface Mount Dimension (HxWxD)	13-9/16 " x 11-1/4 " x 3-3/4 "	N/A
Full-Flush Dimension	N/A	Unit: 13-7/8" x 11-9/16" x 3-3/4" Trim Ring Inside: 13-3/4" x 12" x 3-11/16" Trim Ring Outside: 18" x 15-5/8"
Warranty	24 month	24 month

ACCESSORIES

QVPC Analog color camera USCR 26-Bit Wiegand Satellite Card Reader USKP Satellite keypad USKPR Satellite Card Reader and Keypad Combination UFOB Quantum Keyfob UCLAM Quantum Clam Shell Card UIISO Quantum ISO Card UCRM 26-Bit Wiegand/RS-485 controller Module UWCR 26-Bit Wiegand Card Reader	<u>Pedestal Mounting Post, Adapter Plate and Mounting Ring</u> UPM1S Standard Single Arm (42"H, 5"x5" base) UPM1L Large Single Arm (47"H, 8"x8" base) UPM6L Large Single Arm (64"H, 8"x8" base) UPM2 Double Vertical Arm (44"/84"H, 8"x8" base) UPM5 Double Horizontal Arm (47"H, 8"x8" base) UPM12E 12" Expansion Arm use for all UPM UPMDB64 Single Arm Direct Burial (64"H) UAP09 Adapter plate	<u>Miscellaneous Accessories</u> USP1 AC and Telephone Surge Protector. USP2L Surge and Lightning Protection, <i>include Lightning on 24 months warranty</i> UBAT1 12VDC 4.5 Ahr backup battery. UXIT Multipurpose push button switch IREXIT Infrared exit switch AHP5 Heater-pad
--	--	---