

QUANTUM QVOIP SERIES

MULTI-TENANTS WEB BASED VOIP TELEPHONE ENTRY SYSTEM

10- 600 tenants, 100- 3000 cards and 100-600 codes

Nominal monthly fees and taxes required based on zipcode for activation

Remote programmable, Browser Based

Programming via LAN, WAN, Direct Connect or System's Keypad

No Dedicated IP needed

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box



24 months warranty

Surface and Flush Mount / Indoor or Outdoor, QATA2 Indoor only

FEATURES	QVOIP Surface Mount	QVOIPFF Flush Mount	Q5VOIP Flush Mount	Q5VOIPFF Flush Mount
Input Power Included	12VAC/12VDC	12VAC/12VDC	12VAC/12VDC	12VAC/12VDC
Current Consumption	1200mA	1200mA	1200mA	1200mA
Operating Temperature	10°F to 145°F	10°F to 145°F	10°F to 145°F	10°F to 145°F
Liquid Crystal Display	16 x 1	16 x 1	16 x 1	16 x 1
Tenant Capacity	600	600	10	10
Card Capacity	3000	3000	100	100
Code Capacity	600	600	100	100
26-Bit Wiegand Input	1, card reader is included	1, card reader is included	1, card reader is included	1, card reader is included
Auto Door Schedules	10	10	10	10
Time Zones	10	10	10	10
Holidays	20	20	20	20
Temporary cards/codes	10, 10 times used	10, 10 times used	10, 10 times used	10, 10 times used
Unlock Hold Door	10 cards/codes	10 cards/codes	10 cards/codes	10 cards/codes
Unlock Hold Door Timer	1-98 hours	1-98 hours	1-98 hours	1-98 hours
QWCM IP module	included	included	included	included
AATA2 VOIP (included)	Nominal fees and taxes required based on zip code for activation	Nominal fees and taxes required based on zip code for activation	Nominal fees and taxes required based on zip code for activation	Nominal fees and taxes required based on zip code for activation
Remote access	yes	yes	yes	yes
Dry Contact Relay	2	2	2	2
Door Sensor	2	2	2	2
Intercom mode	n/a	n/a	yes	yes
Auxiliary Input	2, Programmable	2, Programmable	2, Programmable	2, Programmable
Pin hole color camera	optional	optional	optional	optional
Slave Access Control	max. 8	max. 8	max. 8	max. 8
Event report buffer	600	600	600	600
Dimension (HWD)	6-7/16" x 10-3/8" x 3-1/2"	9-13/16" x 11-13/16" x 3-5/8" (TOTAL DIMENSION) 7-1/2" x 10-1/2" x 3-5/8" (INSIDE TRIM-RING)	6-7/16" x 10-3/8" x 3-1/2"	9-13/16" x 11-13/16" x 3-5/8" (TOTAL DIMENSION) 7-1/2" x 10-1/2" x 3-5/8" (INSIDE TRIM-RING)

ACCESSORIES

QVPC: Analog color camera

USP1: AC and Telephone surge protector

USP2L: Surge and Lightning protection

UBAT1: 12VDC 4.5 Ahr backup battery

IREXIT: Infrared exit switch

AHP5: Heater-pad

USCR: Satellite card reader

USKP: Satellite keypad

USKPR: Satellite reader/keypad combo

UCRM: Satellite RS-485 controller

UWCR: 26-Bit card reader

UFOB: Keyfob

UCLAM: Clam shell card

UIISO: ISO card

UPM1S: 42" H Single arm pedestal

UPM2: Dual vertical arm pedestal

UPM5: Dual horizontal arm pedestal

UPM6L: 64" H Single arm pedestal