

# QUANTUM Q9000VOIP SERIES

## MULTI-TENANTS BROWSER BASED VOIP TELEPHONE ENTRY SYSTEM



24 months warranty

900 tenants, 2000 cards and 900 codes

**Nominal monthly fees and taxes required based zip code for activation**

Programming via LAN, WAN, Direct Connect or System's Keypad

No Dedicated IP needed

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount

Indoor or Outdoor, QATA2 Indoor only

FEATURES	Q9000VOIP (Surface Mount)	Q9000VOIPFF (Flush Mount)
Input Power	12VAC/12VDC Transformer Included	12VAC/12VDC Transformer Included
Current Consumption	1200mA	1200mA
Operating Temperature	10°F to 145°F	10°F to 145°F
Liquid Crystal Display	16 x 1, Viewing area 99mm x 13mm	16 x 1, Viewing area 99mm x 13mm
Tenant Capacity	900	900
Card Capacity	2000, <i>card reader is optional</i>	2000, <i>card reader is optional</i>
Code Capacity	900	900
26-Bit Wiegand Input	1, <i>card reader is optional</i>	1, <i>card reader is optional</i>
Auto Door Schedules	10	10
Time Zones	10	10
Holidays	20	20
Temporary cards/codes	10 cards/codes up to 10 times used	10 cards/codes up to 10 times used
Unlock Hold Door with cards/codes	10 cards/codes	10 cards/codes
Unlock Hold Door Timer	1-98 hours	1-98 hours
QWCM ip module	included	included
AATA2 included	<b>Nominal fees and taxes required based on zip code for activation</b>	<b>Nominal fees and taxes required based on zip code for activation</b>
Remote access touch-tone phone	yes	yes
Dry Contact Relay	2	2
Door Sensor	2	2
Postal Lock Ready	yes	yes
Auxiliary Input	2, Programmable	2, Programmable
Analog pin hole color camera	<i>optional</i>	<i>optional</i>
Satellite Access Control RS-485	max. 8 card reader, keypad, or combo	max. 8 card reader, keypad, or combo
Event report	600 buffer	600 buffer
Dimension (HWD)	13-9/16" x 11-1/4" x 3-3/4"	18" x 15-5/8" x 3-3/4" (Total Dimension) 13-3/4" x 12" x 3-11/16" (Inside Ring)

### ACCESSORIES

**QVPC:** Analog color camera  
**USP1:** AC and Telephone surge protector  
**USP2L:** Surge and Lightning protection  
**UBAT1:** 12VDC 4.5 Ahr backup battery  
**IREXIT:** Infrared exit switch  
**AHP5:** Heater-pad

**USCR:** Satellite card reader  
**USKP:** Satellite keypad  
**USKPR:** Satellite reader/keypad combo  
**UCRM:** Satellite RS-485 controller  
**UWCR:** 26-Bit card reader  
**UFOB:** Keyfob

**UCLAM:** Clam shell card  
**UIISO:** ISO card  
**UPM1L:** 46" H Single arm pedestal  
**UPM2:** Dual vertical arm pedestal  
**UPM5:** Dual horizontal arm pedestal