

SCWT SERIES CELLULAR GSM 4G-LTE



SCWT65



SCWT

FEATURES	PART#: SCWT65 OUTDOOR	PART#: SCWT INDOOR
Input Power /Current	12VAC 40VA (supplied)	12VDC 1A (supplied)
Operating Temperature	15°F-145°F	15°F-145°F
LTE Features	B2/B3/B4/B5/B7/B8/B28, TDD: 38/39/40/41, 3G HSPA+: 850/900/1900Mhz	B2/B3/B4/B5/B7/B8/B28, TDD: 38/39/40/41, 3G HSPA+: 850/900/1900Mhz
SIM CARD	Standard SIM Card	Standard SIM Card
Wireless	WIFI 802.11 b/g/n 300Mbps	WIFI 802.11 b/g/n 300Mbps
Antennas	5dBi Internal	5dBi Internal
I/O Interfaces	1 RJ-45 WAN (100 Base-T), 3 RJ-45 LAN (100 Base-T), 2 RJ-11 telephone, SIM Card Slot, Wireless IEEE802.11 b/g/n	1 RJ-45 WAN (100 Base-T), 3 RJ-45 LAN (100 Base-T), 2 RJ-11 telephone, SIM Card Slot, Wireless IEEE802.11 b/g/n
Analog Output Dial Tone	Dual analog Dial Tone Phone1 and Phone2	Dual analog Dial Tone Phone1 and Phone2
4G-LTE GSM Cellular	AT&T	AT&T
Construction	Plastic ABS IP65	Plastic ABS Indoor
Dimension	12-3/5" (H) x 9-1/2" (W) x 4-3/10" (D)	6-1/5" (L) x 4-1/2" (W) / 5-1/2 (with antenna) x 1-1/5" (D)
Warranty	24 months	24 months